









Swivelling hose tails

The swivelling hose tails in Stainless Steel can be used for a swivelling connection between a flexible hose and a spray gun for more comfort in use and longer life of the hoses. Hose tails available in 10mm, 13mm, 16mm and 19mm. The brass versions are equipped with EPDM (FDA) seals and the stainless-steel ones with VITON (FDA) seals. The swivelling hose tails are for the low-pressure environment and can take up to 40 bar.

Up to 24 bar	Reference	Description
	SWIFM1/2	Brass swivelling hose tail 13mm, 1/2" male thread, max. pressure 24 bar
	SWIFR1/2	Stainless steel 316 swivelling hose tail 13mm, 1/2" male thread, max. pressure 24 bar
Up to 40 bar		
	SWIFB10	Stainless Steel 316 swivelling hose tail 10mm x 1/2" male thread, max. pressure 40 bar
	SWIFB13-C17	Stainless Steel 316 swivelling hose tail 13mm x 1/2" male thread and 17mm collar, max. pressure 40 bar
	SWIFB13-C20	Stainless Steel 316 swivelling hose tail 13mm x 1/2" male thread and 20mm collar, max. pressure 40 bar
	SWIFB16-C21	Stainless Steel 316 swivelling hose tail 16mm x 1/2" male thread and 21mm collar, max. pressure 40 bar
	SWIFB19-C24	Stainless Steel 316 swivelling hose tail 19mm x 1/2" male thread and 24mm collar, max. pressure 24 bar
	SWIFB19-C24-34	Stainless Steel 316 swivelling hose tail 19mm x 3/4" male thread and 24mm collar, max. pressure 40 bar

The inside-hose-protection-spring


For the most common dimensions of these swivelling hose tails, versions with welded-on inside-hose-protection-spring are available. This spring ensures that the hose does not kink at the side of the gun and also improves the life of the hose.



Without spring



With spring

	SWIFB13-C17-SP	Stainless Steel swivelling hose tail 13mm x 1/2" male thread and 17mm collar; with spring(20cm)
	SWIFB13-C20-SP	Stainless Steel swivelling hose tail 13mm x 1/2" male thread and 20mm collar; with spring(20cm)
	SWIFB16-C21-SP	Stainless Steel swivelling hose tail 16mm x 1/2" male thread and 21mm collar; with spring(20cm)
	SWIFB19-C24-SP	Stainless Steel swivelling hose tail 19mm x 1/2" male thread and 24mm collar; with spring(20cm)

