

High pressure water gun and lance



Technical data high pressure water gun

Material : Brass / Plastic
 Inlet : 3/8" female thread
 Outlet : Quick release coupler
 Max. pressure : 310 bar
 Max. temperature : 150 °C
 Max. flow : 30 l/min

Technical data high pressure lance

Material : Stainless steel / Plastic
 Inlet : Adapter for quick release coupler
 Outlet : 1/4" female thread
 Max. pressure : 280 bar
 Max. temperature : 150 °C
 Max. flow : 40 l/min

Article number

HDRPIST	High pressure water gun
HDRL070	St.st. lance 70cm without nozzle
HDRL090	St.st. lance 90cm without nozzle
HDRL120	St.st. lance 120cm without nozzle
HDRL070-2506	St.st. lance 70cm with nozzle
HDRL090-2506	St.st. lance 90cm with nozzle
HDRL120-2506	St.st. lance 120cm with nozzle
HDR1070-2506	Watergun with 70cm lance and 2506 nozzle
HDR1090-2506	Watergun with 90cm lance and 2506 nozzle
HDR1200-2506	Watergun with 120cm lance and 2506 nozzle
NOZ2506	St.st. nozzle spray angle 25°, capacity: 100 bar = 14 l/min; 200 bar = 19 l/min <i>(other nozzle available from stock)</i>

OPTIONAL



HDRSWIV-3/8
 High pressure nickel plated brass
 swivel 3/8" male x 3/8" female
 (max. 350 bar / 90 °C)
(Also available in st.st. HDRSWIV-3/8-R)

