

## **Stainless steel couplers and adapters DN20**

This series of couplers and adapters with big bore, 18mm, exist besides the standard version also with non-return valve for as well the coupler as for the adapter. The valve of the coupler can be opened with a standard adapter. However the valve of the adapter can only be opened with the coupler with valve.

		Technical data   Material : AISI 303   Max. pressure : 80 bar   Max. temperature : 100 °C   Seals : COUP20V-1/2F : VITON   : ADAP20V-1/2F : VITON   : COUP200-3/4F : NBR					
	er and adapters DN20		COUP200-3/4F : Coupler with 3/4" female				
	D1d	d	Article no. COUP200-3/4F	<b>L</b> 45,0	<b>d</b> 20,0	D1 3/4"	<b>S</b> 36
COUP200-3/4F		S			L, d en	S in mi	n
		d S	ADAP200-1/2F : Adapter with 1/2" female				
			ADAP200-3/4F : Adapter with 3/4" female				
			Article no.	L	d	D1	S
			ADAP200-1/2F ADAP200-3/4F	46,0 46,0	18,0 18,0	1/2" 3/4"	26 36
ADAP200-1/2F		L, d en S in mm					
ADAP200-3/4F	Also fits with COUI						
Quick release coupler and adapters DN20 with valve							
			COUP20V-1/2F : Coupler with valve, 1/2" female				
			Article no.	L	d	D1	S
		i S i	COUP20V-1/2F	76,7	20,0	1/2"	36
COUP20V-1/2F			L, d en S in mm				
		G	ADAP20V-1/2F : Adapter with valve, 1/2" female				
	D1		Article no.	L	d	D1	S
			ADAP20V-1/2F	76,7	18,0	1/2"	36
ADAP20V-1/2F	Does <u>not</u> fit COUP	L, d en S in mm					

