

Ball-bearing swivels



AKBO ball-bearing swivels are available in brass, chrome-plated brass and stainless steel (AISI 316).

Using a ball-bearing swivel on a hose with a water gun will have a positive effect on operator comfort and hose life. The brass swivel fittings have EPDM (FDA) seals, while the stainless steel versions have VITON (FDA) seals.

The swivels can be used up to an operating pressure of 30 bar and up to a temperature of 95 °C.

Other sizes are available on request (only for high quantities).

Male x Female																																																															
			<p align="center">Sizes L, d, S1 and S2 in mm</p> <table border="1"> <thead> <tr> <th>Brass</th> <th>Chrome-plated brass</th> <th>Stainless steel</th> <th>L</th> <th>d</th> <th>D1</th> <th>D2</th> <th>S1</th> <th>S2</th> </tr> </thead> <tbody> <tr> <td>SWM09-12</td> <td>SWC09-12</td> <td>SWR09-12</td> <td>40</td> <td>9</td> <td>1/2"</td> <td>1/2"</td> <td>27</td> <td>27</td> </tr> <tr> <td>SWM09-34</td> <td>SWC09-34</td> <td>SWR09-34</td> <td>40</td> <td>9</td> <td>3/4"</td> <td>1/2"</td> <td>30</td> <td>27</td> </tr> <tr> <td>SWM14-34</td> <td></td> <td>SWR14-34</td> <td>49</td> <td>14</td> <td>3/4"</td> <td>1/2"</td> <td>30</td> <td>27</td> </tr> <tr> <td>SWM14-34x34</td> <td></td> <td>SWR14-34x34</td> <td>46/ - /44</td> <td>14</td> <td>3/4"</td> <td>3/4"</td> <td>30</td> <td>30</td> </tr> <tr> <td>SWM18-1x1</td> <td></td> <td>SWR18-1x1</td> <td>49</td> <td>18</td> <td>1"</td> <td>1"</td> <td>36</td> <td>36</td> </tr> </tbody> </table>							Brass	Chrome-plated brass	Stainless steel	L	d	D1	D2	S1	S2	SWM09-12	SWC09-12	SWR09-12	40	9	1/2"	1/2"	27	27	SWM09-34	SWC09-34	SWR09-34	40	9	3/4"	1/2"	30	27	SWM14-34		SWR14-34	49	14	3/4"	1/2"	30	27	SWM14-34x34		SWR14-34x34	46/ - /44	14	3/4"	3/4"	30	30	SWM18-1x1		SWR18-1x1	49	18	1"	1"	36	36
Brass	Chrome-plated brass	Stainless steel	L	d	D1	D2	S1	S2																																																							
SWM09-12	SWC09-12	SWR09-12	40	9	1/2"	1/2"	27	27																																																							
SWM09-34	SWC09-34	SWR09-34	40	9	3/4"	1/2"	30	27																																																							
SWM14-34		SWR14-34	49	14	3/4"	1/2"	30	27																																																							
SWM14-34x34		SWR14-34x34	46/ - /44	14	3/4"	3/4"	30	30																																																							
SWM18-1x1		SWR18-1x1	49	18	1"	1"	36	36																																																							

Male x Male																																				
<p align="center">On request</p>			<table border="1"> <thead> <tr> <th>Brass</th> <th>Chrome-plated brass</th> <th>Stainless steel</th> <th>L</th> <th>d</th> <th>D1</th> <th>D2</th> <th>S1</th> <th>S2</th> </tr> </thead> <tbody> <tr> <td>SWM09-12Mx12M</td> <td></td> <td>SWR09-12Mx12M</td> <td>46</td> <td>9</td> <td>1/2"</td> <td>1/2"</td> <td>27</td> <td>27</td> </tr> <tr> <td>SWM09-12Mx34M</td> <td></td> <td>SWR09-12Mx34M</td> <td>48</td> <td>9</td> <td>3/4"</td> <td>1/2"</td> <td>27</td> <td>27</td> </tr> </tbody> </table>							Brass	Chrome-plated brass	Stainless steel	L	d	D1	D2	S1	S2	SWM09-12Mx12M		SWR09-12Mx12M	46	9	1/2"	1/2"	27	27	SWM09-12Mx34M		SWR09-12Mx34M	48	9	3/4"	1/2"	27	27
Brass	Chrome-plated brass	Stainless steel	L	d	D1	D2	S1	S2																												
SWM09-12Mx12M		SWR09-12Mx12M	46	9	1/2"	1/2"	27	27																												
SWM09-12Mx34M		SWR09-12Mx34M	48	9	3/4"	1/2"	27	27																												

Flat seals		Sizes in mm			
EPDM (FDA)	Viton (FDA)	d	D	H	
Male thread	Male thread				
SWSEM 1/2	SWSVM 1/2	17	26	2	
SWSEM 3/4	SWSVM 3/4	23,5	32	2	
Female thread	Female thread				
SWSEF 1/2	SWSVF 1/2	11	23	2	
SWSEF 3/4	SWSVF 3/4	15	27	2	