

NiTO “Click” couplings

Compatible with most popular plastic couplings

Technical specifications

Material	Chrome plated brass
Seal	NBR / EPDM
Max. pressure	25 bar
Max. temp.	-30 °C to +80 °C



1/2" Series			
Photo	Article number		Description
	1/2" Series	3/4" Series	
	AK59820A3		NITO CLICK 1/2" coupler with 1/2" NITO adapter
	AK59810A3		NITO coupler with 1/2" CLICK adapter
	AK5952GA3		NITO CLICK coupler with M22x1, 1/2" and 3/4" BSP female thread
		AK69500A3	NITO CLICK coupler with 3/4" BSP female thread
	AK5950NA3		NITO CLICK coupler with 1/2" BSP male thread
	AK5949SA3		NITO CLICK coupler with 3/8" hose tail
	AK5950SA3		NITO CLICK coupler with 1/2" hose tail
	AK5950CA3		NITO CLICK coupler with 5/8" hose tail
	AK5951SA3	AK6950SA3	NITO CLICK coupler with 3/4" hose tail
	AK59610A3		NITO CLICK adapter with 1/2" BSP female thread
	AK5961GA3		NITO CLICK adapter with M22x1, 1/2" and 3/4" BSP male thread
		AK69610A3	NITO CLICK adapter with 3/4" BSP female thread
	AK59640A3		NITO CLICK adapter with 1/2" BSP male thread
	AK5964AA3	AK69640A3	NITO CLICK adapter with 3/4" BSP male thread
	AK59600A3	AK6960BA3	NITO CLICK adapter with 1/2" hose tail
		AK69600A3	NITO CLICK adapter with 3/4" hose tail
	AK5960AA3		NITO CLICK adapter with 1/2" + 3/4" hose tail